
**CURTAINWALL SYSTEM** 


#### SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

PART # DESCRIPTION PROPERTIES DRAWING

BAM-20400 2.5 X 4 MULL  $Ix = 5.533^{*4} Sx = 2.014^{*3}$ 

 $ly = 1.714"^4 Sy = 1.321"^3$ 





WINDLOAD CHARTS ARE PROVIDED AS A CONVENIENCE FOR DESIGN PURPOSES ONLY. DEFLECTION IS AT L/240+1/4; OR AT L/175 AT <162."

THEY PROVIDE A CLOSE ESTIMATE, BUT SHOULD BE CONFIRMED BY THE PROJECT ENGINEER.
BOYD ALUMINUM RESERVES THE RIGHT TO REVISE ANY PUBLISHED INFORMATION WITHOUT NOTICE AND WILL NOT BE RESPONSIBLE

FOR UNCHECKED, OUT OF DATE, OR MISUSED INFORMATION.


**CURTAINWALL SYSTEM** 


#### SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

PART # DESCRIPTION PROPERTIES DRAWING

BAM-20404 2.5 X 4 SSG MULL  $Ix = 3.687^{"4} Sx = 1.762^{"3}$ 

ly = 1.671" sy = 1.336"





WINDLOAD CHARTS ARE PROVIDED AS A CONVENIENCE FOR DESIGN PURPOSES ONLY. DEFLECTION IS AT L/240+1/4; OR AT L/175 AT <162."

THEY PROVIDE A CLOSE ESTIMATE, BUT SHOULD BE CONFIRMED BY THE PROJECT ENGINEER.

BOYD ALUMINUM RESERVES THE RIGHT TO REVISE ANY PUBLISHED INFORMATION WITHOUT NOTICE AND WILL NOT BE RESPONSIBLE FOR UNCHECKED, OUT OF DATE, OR MISUSED INFORMATION.


**CURTAINWALL SYSTEM** 


#### SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

PART # DESCRIPTION PROPERTIES DRAWING

BAM-20500 2.5 X 5 MULL Ix = 8.977" Sx = 2.971"

 $ly = 2.068"^4 Sy = 1.600"^3$ 





WINDLOAD CHARTS ARE PROVIDED AS A CONVENIENCE FOR DESIGN PURPOSES ONLY. DEFLECTION IS AT L/240+1/4; OR AT L/175 AT <162."

THEY PROVIDE A CLOSE ESTIMATE, BUT SHOULD BE CONFIRMED BY THE PROJECT ENGINEER.
BOYD ALUMINUM RESERVES THE RIGHT TO REVISE ANY PUBLISHED INFORMATION WITHOUT NOTICE AND WILL NOT BE RESPONSIBLE FOR UNCHECKED, OUT OF DATE, OR MISUSED INFORMATION.


**CURTAINWALL SYSTEM** 


#### SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

PART # DESCRIPTION PROPERTIES DRAWING

BAM-20504 2.5 X 5 SSG MULL  $Ix = 6.357^{4} Sx = 2.441^{3}$ 

 $ly = 2.024"^4 Sy = 1.618"^3$ 





WINDLOAD CHARTS ARE PROVIDED AS A CONVENIENCE FOR DESIGN PURPOSES ONLY. DEFLECTION IS AT L/240+1/4; OR AT L/175 AT <162."

THEY PROVIDE A CLOSE ESTIMATE, BUT SHOULD BE CONFIRMED BY THE PROJECT ENGINEER.

BOYD ALUMINUM RESERVES THE RIGHT TO REVISE ANY PUBLISHED INFORMATION WITHOUT NOTICE AND WILL NOT BE RESPONSIBLE FOR UNCHECKED, OUT OF DATE, OR MISUSED INFORMATION.


#### **CURTAINWALL SYSTEM**


#### SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

PART # DESCRIPTION PROPERTIES DRAWING

BAM-20800 2.5 X 8 MULL Ix = 28.64" Sx = 6.077"

ly = 3.441" sy = 2.689"





WINDLOAD CHARTS ARE PROVIDED AS A CONVENIENCE FOR DESIGN PURPOSES ONLY. DEFLECTION IS AT L/240+1/4; OR AT L/175 AT <162."

THEY PROVIDE A CLOSE ESTIMATE, BUT SHOULD BE CONFIRMED BY THE PROJECT ENGINEER.

BOYD ALUMINUM RESERVES THE RIGHT TO REVISE ANY PUBLISHED INFORMATION WITHOUT NOTICE AND WILL NOT BE RESPONSIBLE FOR UNCHECKED, OUT OF DATE, OR MISUSED INFORMATION.


**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

PART # DESCRIPTION PROPERTIES DRAWING

BAM-20804 2.5 X 8 SSG MULL  $Ix = 22.75^{4} Sx = 5.529^{3}$ 

 $ly = 3.401"^4 Sy = 2.721"^3$ 






WINDLOAD CHARTS ARE PROVIDED AS A CONVENIENCE FOR DESIGN PURPOSES ONLY. DEFLECTION IS AT L/240+1/4; OR AT L/175 AT <162."

THEY PROVIDE A CLOSE ESTIMATE, BUT SHOULD BE CONFIRMED BY THE PROJECT ENGINEER. BOYD ALUMINUM RESERVES THE RIGHT TO REVISE ANY PUBLISHED INFORMATION WITHOUT NOTICE AND WILL NOT BE RESPONSIBLE FOR UNCHECKED, OUT OF DATE, OR MISUSED INFORMATION.


**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS



**CURTAINWALL SYSTEM** 


#### SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS






**CURTAINWALL SYSTEM** 

SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS





**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

PART # DESCRIPTION PROPERTIES DRAWING
6.000

BAM-20404


2.5 X 4 SSG MULL Ix = 3.687" Sx = 1.762" 2.500


Iy = 1.671" Sy = 1.336" 2.500



**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS






**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS



**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS






**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS






**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS






**CURTAINWALL SYSTEM** 

SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS






**CURTAINWALL SYSTEM** 

SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS


PART # DESCRIPTION PROPERTIES DRAWING


BAM-20506 2.5 X 5 IG HORZ  $Ix = 6.856^{"}^{4} Sx = 2.166^{"}^{3}$   $Iy = 0.288^{"}^{4} Sy = 0.410^{"}^{3}$ 



**CURTAINWALL SYSTEM** 

SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS







**CURTAINWALL SYSTEM** 


SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

PART # DESCRIPTION PROPERTIES DRAWING

BAM-20800 2.5 X 8 MULL  $Ix = 28.64^{-4} Sx = 6.077^{-3}$ 







**CURTAINWALL SYSTEM** 

SEE TOOLING FOR PROPER USE & COMPINATIONS OF EXTRUSIONS

 PART #
 DESCRIPTION
 PROPERTIES
 DRAWING

 BAM-20804
 2.5 X 8 SSG MULL
 Ix = 22.75" Sx = 5.529" Sx = 5.529" Sx = 5.529"
 IX = 22.75" Sx = 5.529" Sx = 5.529"

